

StroBell - Combined Fire Bell & Strobe Indicator

A combined bell and strobe with high sound and light output.

Using the market leading aluminium gong for excellent sound output and a clear lens to maximise light output, the VimpeX StroBell is ideal for installations that call for a traditional bell tone but require visual indication as well.

As with the VimpeX sounder range, all bells can be supplied branded with your company logo.

Features

- Utilises market-leading bell design
- Ultra bright strobe in clear lens for maximum light output
- Familiar installation method
- Selectable flash rate - 30/60 per minute
- Low current consumption
- Single point of installation minimises wiring and associated costs



Specification

Rated Voltage:	24 Vdc ±20%
Starting Voltage:	16 Vdc
Sound output @ 1m (max):	95 dB(A)
Rated Current @ 24 Vdc:	Bell only, 11 mA 30 flashes/min (0.5 Hz), 30 mA 60 flashes/min (1.0 Hz), 50 mA
Light Output (at front):	> 15 Candela
Flash Rate:	0.5 or 1.0 Hz selectable
Gong Colour:	Red
Gong construction:	Aluminium
IP Rating (minimum):	IP21 - For internal use only
Weight:	579 g
Operating Temp Range:	-20 to +55 °C

Standards

- Conforms to EN-55022 and EMC Directive 89/336/EEC

Part Number

SMBF-6EV: Strobell Red

VimpeX Limited

Star Lane, Great Wakering
Essex SS3 0PJ England
Tel: +44 (0) 1702 216999
Fax: +44 (0) 1702 216699
E-mail: sales@vimpeX.co.uk
www.vimpeX.co.uk



Assessed to ISO 9001
Cert/LPCB ref. 456



Shaping Alarm Technology

Installation

